

Maximum Flexibility is the hallmark of the Nautilus Hyosung 7600FFL. Options for ease of servicing - front or rear safe enclosure access provide you with ideal installation choices. Options for deposit processing technologies allow your institution to custom tailor solutions to cardholder preferences. Security options that enable you to rest assured - all in a very functional, high capacity interior lobby device.

Features

Market Strength Capabilities

The 7600FFL supports a full range of personalization, advertising, and marketing options as well as end to end deposit automation implementations. An attention grabbing 15.1" color TFT supports these functions. As with all Nautilus Hyosung platforms, the modules are designed, engineered, manufactured and tested in house with 24/7 unattended self-service functionality as their design goal. This means the 7600FFL is as reliable as it is functional - with a migration path for institutions with vision.

Security

The 7600FFL's UL-291 Level 1 rated safe has been proven in the field time and again. Additional standard features like the EPP PIN shield and over the shoulder assurance mirrors maximize customer privacy and enhance safety. Certified keyboards give you the ability to comply with PCI EPP requirements, and optional security cameras for both surveillance and cash withdrawal areas allow you to protect both your customers and your cash assets at the ATM. Optional software and transactional security features are available.

Dependability

Reliability derived from being the market leader in cash dispensing technology, and availability provided by high capacity modules, the 7600FFL is the ideal self-service platform for full function interior lobby deployments.

Monimax 7600FFL is designed with "customerization" in mind. The most deployment options, the fullest feature/function options in a robust secure platform. The 7600FFL enables efficient service events enhanced by access by design, and quick deployments enabled by platform flexibility. Users will appreciate the clean, compact interface. All in one highly secure, reliable platform.



Hyosung - Always By Your Side. Nautilus Hyosung is more than reliable, proven self service technology. We are a company dedicated to the success of our partners.

System Control

- Intel® processor
- Microsoft® Windows® XP platform
- NDC+, User Application

Communication

- TCP/IP
- Wireless X.25 capable

Customer Display

- 15" color TFT LCD Touch Screen

Optional

- Privacy filter
- Sunlight readable

Input Type

- PCI compliant EPP
- ADA compliant

Card Handling

- Dip-type card reader

Optional

- Anti-skimming

Supervisor Operation

- 15" TFT color LCD, touch screen

Cash Dispensing

- 3,000 notes cassette
(Up to 4 cassettes)
- Bundle retraction
- Automatic shutter

Depository Options

- Bulk check acceptor
- Bulk note acceptor
- Envelope depository

Printers

- 3.1" graphical thermal receipt printer
- 5,000 transactions
- Electronic journal

Security

- UL 291 Level 1
- Electronic lock
- KABA Mas Cencon lock

Optional

- Mechanical combination lock
- Camera
- Heater

Power Supply

- AC 110 – 240V, 50–60Hz
- Back-up battery

Operating Environment

- Temperature: 31°F – 104°F

Optional

- Humidity: 25% – 85%

Dimension and Weight

- Height : 66.1" (1,677.9 mm)
- Width : 30.3" (770 mm)
- Depth : 44.2" (1,121.7 mm)
- Weight : 1,984.1 lbs (900 kg)

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.



15" color customer display
 • Optional sunlight viewable

3.1" graphical thermal
 receipt printer

PCI-compliant EPP

Cash dispenser

Bulk note acceptor
 Optional envelope depository

Optional VFD
 (Vacuum Fluorescent Display)

Security camera (optional)

Bulk check acceptor

Card reader