

## Freestanding Full-Function Island Drive-Up ATM

The Monimax 7600i is an advanced multi-functional free-standing island, drive-up ATM designed to provide maximum reliability, security, and convenience.

### Features

An industry-first **automatic tilting screen** ensures maximum ATM banking convenience for your customers to suit various vehicle heights.

Proven deposit automation technology is provided from in-house designed and manufactured envelope-free deposit modules.

### Easy to deploy, highly reliable

The Monimax 7600i's footprint allows easy installation into virtually any existing location.

The Monimax 7600i provides continual deposit and cash service to customers with industry-leading uptime rates.

### Enhanced Security

The 7600i is equipped with dual UL level 1 safes for the depository and cash dispensing unit. Advanced security features include heat and vibration sensors, security alarms, and anti-skimming devices.



### Automatic tilting screen

Customers can adjust the tilting touch screen to their vehicle height. The screen angles upward to accommodate higher vehicles and SUVs.

## System Control

- Microsoft® Windows XP® platform
- Intel® processor
- NDC+, User Application

## Customer Display

- 15" color TFT LCD
- Sunlight readable touch screen
- Optional**
- Privacy filter

## Communication

- TCP/IP
- Optional**
- Wireless. X.25 capable

## Input Type

- PCI EPP (Encrypting PIN pad)
- ADA compliant
- Optional**
- Tilting screen

## Supervisor Operation

- TFT color LCD, touch screen

## Card Handling

- Dip-type card reader
- Optional**
- Anti-skimming

## Cash Dispensing

- 3,000-notes cassette, up to four cassettes
- Bundle retraction
- Automatic shutter

## Depository Options

- Envelope depository
- Bulk check acceptor
- Bulk note acceptor

## Printers

- 3.1" graphical thermal receipt printer
- 5,000 transaction receipt printer
- Electronic journal

## Security

- UL291 Level 1 safe
- Enhanced Alarms
- Electronic safe lock
- Optional**
- KABA Mas Cencon safe lock
- security camera

## Miscellaneous

- Lead-through indicator
- Illuminated signage
- Rear-view mirror
- Optional**
- Extreme-weather heater

## Power Supply


- AC 110–240V, 50–60 Hz
- Back-up battery

## Operating Environment

- Temperature: -31°F–122°F (-35 °C–50 °C)
- Humidity: 5%–85%  
(with climate control device)

## Dimension and Weight

- Height: 56.7" (1,439 mm)
- Width: 41.3" (1,048 mm)
- Depth: 36" (914.4 mm)
- Weight: 2,182 lbs (990 kg) w/ env. deposit  
(Preliminary specifications, subject to change)



NH 7600i  
001\_06/2011